

Pressure	bar(g)	8	10	12
1st row: Free air delivery* (m ³ /min)	8	2,25		
		14,51		
		15,60		
2nd row: Shaft Power* (kW)	10			1,97
				13,86
				14,90
3rd row: Terminal Power (incl. Fan)* (kW)	12			1,79
				16,28
				17,50
Sound Level	dB(A)	65 +/-2		
Air Discharge Temperature over Ambient	K	≤15		
Tank for TD version	l	2x125		
Controller	MAM-6080			
Electrical Data				
Voltage / Frequency	400V / 50Hz			
Rated Motor Power	kW	15		
Motor speed	1/min	2930		
Starting method	Star/Delta			
Efficiency Class	IE-3			
Enclosure / ISO Class	IP 54 / F			
Rated Fan Motor Power	kW	0,37		
Fan Drive	Fixed			
Rated Dryer Power	kW	0,28		
Recommed cross-section, lenght 10M	10mm ²			
Fuse (Type gG)	A	40		
Cooling Data				
Type of cooling	Air Cooling			
Cooling air capacity	m ³ /h	2.100		
Ambient Temperature	°C	+5 - +45		
Dimensions, Weight ...				
Dimension Stand Alone (l x w x h)	mm	1030 x 850 x 1280		
Dimension with Tank&Dryer (l x w x h)	mm	1962 x 920 x 1765		
Weight Stand Alone	kg	360		
Weight with Tank&Dryer	kg	580		
Compressed Air Outlet Stand Alone	3/4"			
Compressed Air Outlet Tank&Dryer	1"			
Oil Capacity	l	8		
Residual Oil Content	mg/m ³	3-5		

* Measurement of data according to ISO1217 Annex C / E

Technical changes reserved.

Copyright@Tolpec GmbH