

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding Permanent Ink (black) contained in: edding 8407 cable marker**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Ink for use in felt pens

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

1-methoxy-2-propanol

**Hazard statement(s)**

H225

Highly flammable liquid and vapour.

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Precautionary statement(s)**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 Use only outdoors or in a well-ventilated area.  
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.  
P405 Store locked up.  
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**

**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name	Classification (EC) 1272/2008 (CLP)	Additional information	%
	CAS / EC / Index / REACH no		Concentration	
1	<b>1-methoxy-2-propanol</b>			
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35-0034	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25.00 - < 50.00	wt%
2	<b>Reaction mass of hydrogen [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] chromate (1-), compound with 3 - [(2-ethylhexyl) oxy] propylamine (1: 1)</b>			
	- 916-881-8 - 01-2120763683-46	-	>= 10.00 - < 25.00	wt%
3	<b>ethanol</b>			
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225	>= 10.00 - < 25.00	wt%
4	<b>propan-2-ol</b>			
	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-0085	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 10.00 - < 25.00	wt%
5	<b>hydrogen bis[2,4-dihydro-4-[(2-hydroxy-4-nitrophenyl)azo]-5-methyl-2 phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)</b>			

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

33270-70-1 251-436-5 - -	-	<	2.50	wt%
-----------------------------------	---	---	------	-----

Full Text for all H-phrases and EUH-phrases: pls. see section 16

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash immediately with plenty of water for several minutes.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide

#### Unsuitable extinguishing media

No data available.

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

### 5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

### 6.3 Methods and material for containment and cleaning up

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

#### 6.4 Reference to other sections

No data available.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

##### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

##### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

##### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

#### 7.3 Specific end use(s)

No data available.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Comments	Sk	
2	Reaction mass of hydrogen [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] chromate (1-), compound with 3 - [(2-ethylhexyl) oxy] propylamine (1: 1)		916-881-8
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Chromium (VI) compounds (as Cr)		

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

	WEL long-term (8-hr TWA reference period)	0.01	mg/m <sup>3</sup>		
	Comments	Carc, sen, BMGV			
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Chromium (VI) compounds (as Cr)					
	WEL long-term (8-hr TWA reference period)	0,025	mg/m <sup>3</sup>		
		(process generated) <sup>1</sup>			
	Comments	Carc, sen, BMGV			
<b>2004/37/EC</b>					
Chromium (VI) compounds					
	WEL long-term (8-hr TWA reference period)	0.005	mg/m <sup>3</sup>		
	Comments	Limit value 0,010 mg/m <sup>3</sup> until 17 January 2025 Limit value: 0,025 mg/m <sup>3</sup> for welding or plasma cutting processes or similar work processes that generate fume until 17 January 2025			
<b>3</b>	<b>ethanol</b>	<b>64-17-5</b>		<b>200-578-6</b>	
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Ethanol					
	WEL long-term (8-hr TWA reference period)	1920	mg/m <sup>3</sup>	1000	ppm
<b>4</b>	<b>propan-2-ol</b>	<b>67-63-0</b>		<b>200-661-7</b>	
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Propan-2-ol					
	WEL short-term (15 min reference period)	1250	mg/m <sup>3</sup>	500	ppm
	WEL long-term (8-hr TWA reference period)	999	mg/m <sup>3</sup>	400	ppm
<b>5</b>	<b>hydrogen bis[2,4-dihydro-4-[(2-hydroxy-4-nitrophenyl)azo]-5-methyl-2 phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)</b>	<b>33270-70-1</b>		<b>251-436-5</b>	
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Chromium (VI) compounds (as Cr)					
	WEL long-term (8-hr TWA reference period)	0.01	mg/m <sup>3</sup>		
	Comments	Carc, sen, BMGV			
<b>List of approved workplace exposure limits (WELs) / EH40</b>					
Chromium (VI) compounds (as Cr)					
	WEL long-term (8-hr TWA reference period)	0,025	mg/m <sup>3</sup>		
		(process generated) <sup>1</sup>			
	Comments	Carc, sen, BMGV			
<b>2004/37/EC</b>					
Chromium (VI) compounds					
	WEL long-term (8-hr TWA reference period)	0.005	mg/m <sup>3</sup>		
	Comments	Limit value 0,010 mg/m <sup>3</sup> until 17 January 2025 Limit value: 0,025 mg/m <sup>3</sup> for welding or plasma cutting processes or similar work processes that generate fume until 17 January 2025			

### DNEL, DMEL and PNEC values

#### DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	dermal	Long term (chronic)	systemic	183	mg/kg/day
	inhalative	Long term (chronic)	systemic	369	mg/m <sup>3</sup>
	inhalative	Short term (acut)	local	553.5	mg/m <sup>3</sup>
2	ethanol			64-17-5 200-578-6	
	dermal	Long term (chronic)	systemic	343	mg/kg/day
	inhalative	Long term (chronic)	systemic	950	mg/m <sup>3</sup>

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

3	<b>propan-2-ol</b>			<b>67-63-0</b> <b>200-661-7</b>	
	dermal	Long term (chronic)	systemic	888	mg/kg/day
	inhalative	Long term (chronic)	systemic	500	mg/m <sup>3</sup>

**DNEL value (consumer)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	<b>1-methoxy-2-propanol</b>			<b>107-98-2</b> <b>203-539-1</b>	
	oral	Long term (chronic)	systemic	33	mg/kg/day
	dermal	Long term (chronic)	systemic	78	mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9	mg/m <sup>3</sup>
2	<b>ethanol</b>			<b>64-17-5</b> <b>200-578-6</b>	
	oral	Long term (chronic)	systemic	87	mg/kg/day
	dermal	Long term (chronic)	systemic	206	mg/kg/day
	inhalative	Short term (acut)	local	950	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	systemic	114	mg/m <sup>3</sup>
3	<b>propan-2-ol</b>			<b>67-63-0</b> <b>200-661-7</b>	
	oral	Long term (chronic)	systemic	26	mg/kg/day
	dermal	Long term (chronic)	systemic	319	mg/kg/day
	inhalative	Long term (chronic)	systemic	89	mg/m <sup>3</sup>

**PNEC values**

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	<b>1-methoxy-2-propanol</b>		<b>107-98-2</b> <b>203-539-1</b>	
	water	fresh water	10	mg/L
	water	marine water	1	mg/L
	water	Aqua intermittent	100	mg/L
	water	fresh water sediment	52.3	mg/kg
	with reference to: dry weight			
	water	marine water sediment	5.2	mg/kg
	with reference to: dry weight			
	soil	-	4.59	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L
2	<b>ethanol</b>		<b>64-17-5</b> <b>200-578-6</b>	
	water	fresh water	0.96	mg/L
	water	marine water	0.79	mg/L
	water	fresh water sediment	3.6	mg/kg
	with reference to: dry weight			
	water	Aqua intermittent	2.75	mg/L
	water	marine water sediment	2.9	mg/kg
	with reference to: dry weight			
	soil	-	0.63	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	580	mg/L
	secondary poisoning	-	0.38	g/kg
	with reference to: food			
3	<b>propan-2-ol</b>		<b>67-63-0</b> <b>200-661-7</b>	
	water	fresh water	140.9	mg/L
	water	Aqua intermittent	140.9	mg/L
	water	marine water	140.9	mg/L
	water	fresh water sediment	552	mg/L
	water	marine water sediment	552	mg/L

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

soil	-	28	mg/kg
sewage treatment plant	-	2251	mg/L
secondary poisoning	-	160	mg/kg
with reference to: food			

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

#### Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form</b>	
liquid	
<b>Colour</b>	
black	
<b>Odour</b>	
weak	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	78 °C
Reference substance	CAS 64-17-5
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	13 °C
Reference substance	CAS 64-17-5
<b>Ignition temperature</b>	
No data available	

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

<b>Flammability</b>			
No data available			
<b>Lower explosion limit</b>			
Value	1.9	% vol	
<b>Upper explosion limit</b>			
Value	13.1	% vol	
<b>Vapour pressure</b>			
No data available			
<b>Relative vapour density</b>			
No data available			
<b>Relative density</b>			
Value	0.992		
<b>Density</b>			
No data available			
<b>Solubility in water</b>			
Comments	insoluble		
<b>Solubility</b>			
No data available			
<b>Partition coefficient n-octanol/water (log value)</b>			
<b>No</b>	<b>Substance name</b>	<b>CAS no.</b>	<b>EC no.</b>
1	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source	ECHA		
<b>Kinematic viscosity</b>			
No data available			
<b>Particle characteristics</b>			
No data available			

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

Heat; air humidity

### 10.5 Incompatible materials

No data available.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		
2	ethanol	64-17-5	200-578-6
LD50		10740	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
3	propan-2-ol	67-63-0	200-661-7
LD50		5840	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

<b>Acute dermal toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		

<b>Acute inhalational toxicity</b>			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124.7	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
2	propan-2-ol	67-63-0	200-661-7
LC50	>	10000	ppmV
Duration of exposure		6	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

<b>Skin corrosion/irritation</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		
2	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

<b>Serious eye damage/irritation</b>			
No	Substance name	CAS no.	EC no.

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		
2	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		

#### Respiratory or skin sensitisation

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure		Skin	
Species	guinea pig		
Method	440/2008/EC B.6		
Source	ECHA		
Evaluation	non-sensitizing		
2	ethanol	64-17-5	200-578-6
Route of exposure		Skin	
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
3	propan-2-ol	67-63-0	200-661-7
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		

#### Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

#### Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

#### Carcinogenicity

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
Route of exposure		inhalational	
Source		ECHA	

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

Evaluation/classification	Based on available data, the classification criteria are not met.
---------------------------	---

#### Aspiration hazard

No data available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

No data available.

#### Other information

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Toxicity to fish (acute)

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50	>	14000	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA E03-05		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
LC50	>	9640	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		

#### Toxicity to fish (chronic)

No data available

#### Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
EC50	>	10000	mg/l
Duration of exposure		24	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

#### Toxicity to Daphnia (chronic)

No data available

#### Toxicity to algae (acute)

No data available

#### Toxicity to algae (chronic)

No data available

#### Bacteria toxicity

No data available

### 12.2 Persistence and degradability

#### Biodegradability

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

Value	96	%
Duration	28	day(s)
Method	OECD 301 E	
Source	ECHA	
Evaluation	readily biodegradable	
<b>2</b>	<b>propan-2-ol</b>	<b>67-63-0</b> <b>200-661-7</b>
Type	BOD/COD	
Value	53	%
Duration	5	day(s)
Source	ECHA	
Evaluation	readily biodegradable	

### 12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source	ECHA		

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Endocrine disrupting properties

No data available.

### 12.7 Other adverse effects

No data available.

### 12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

### 14.2 Transport IMDG

Class	3
-------	---

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

Packing group II  
 UN number UN1263  
 Proper shipping name PAINT  
 EmS F-E, S-E  
 Label 3

#### 14.3 Transport ICAO-TI / IATA

Class 3  
 Packing group II  
 UN number UN1263  
 Proper shipping name Paint  
 Label 3

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

No data available.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulations

##### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

##### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

##### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	hydrogen bis[2,4-dihydro-4-[(2-hydroxy-4-nitrophenyl)azo]-5-methyl-2 phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)	33270-70-1	251-436-5	75
2	propan-2-ol	67-63-0	200-661-7	75
3	Reaction mass of hydrogen [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -) ] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -) ] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] chromate (1-), compound with 3 - [(2-ethylhexyl) oxy] propylamine (1: 1)	-	916-881-8	75

##### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

**Trade name:** edding Permanent Ink (black) contained in: edding 8407 cable marker

**Current version :** 2.1.3, issued: 27.10.2022

**Replaced version:** 2.1.2, issued: 15.09.2021

**Region:** GB

This product is subject to Part I of Annex I, risk category:

P5b

## 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

### Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour.

### Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

### Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 615037